

## MATERIAL SAFETY DATA SHEET

**PRODUCT:** GLASS FIBRE REINFORCED TAPE  
**REF:** DM0170  
**DATE OF ISSUE:** January 2007  
**SUPPLIER:** Partwell Cutting Technology Specialists  
Bridge Works, Stanley Street, Blackburn, Lancs. BB1 3BW  
Tel: 01254 671875 Fax: 01254 674823

### **DESCRIPTION**

Crossweave glass-fibre reinforced tape coated with a synthetic rubber resin adhesive (hotmelt).

### **APPLICATIONS**

Strapping, Bundling, Carton Sealing

### **TECHNICAL DETAILS**

Total thickness: 0.125mm  
Backing thickness: 0.03 mm  
Tensile strength: 240 n/cm  
Elongation: 10%  
Temperature: 0°C TO 60°C  
Steel adhesion: 5 n/cm  
Colours: Clear

### NOTE:

Unless otherwise specified, the figures above are average values and should not be treated at face value for specification purposes. The company reserves the right to improve products, and any change in specification will result in re-issue of the information sheet. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modification or otherwise. Please check that you have the latest issue of the information sheet. All slitting and length tolerances are to British standards.