

POLYPROPYLENE

CO-POLYMER

MECHANICAL PROPERTIES

Density	ISO 1183	g/cm ³	0.901
Tensile Stress at Yield	ISO 527-1	N/mm ²	25
Modulus of elasticity in tension	ISO 527-1	N/mm ²	1100
Elongation at break	ISO 527-1	%	>50
Hardness shore D	ISO 868	points	69
Notched impact strength	ISO 179	mJ/mm ²	>40

Technical Data Sheet

FURTHER INFORMATION

THERMAL PROPERTIES

Vicat Softening temperature VSP/b/50	ISO 306	°C	85
Co efficient of Linear Expansion	DIN 53752	1/K	1-2*10 ⁻⁴
Fire Behaviour	HB		UL94
Operating Temperature	Short Term	°C	-30....150
	Long Term	°C	-30....100

ELECTRICAL PROPERTIES

Insulation Resistance	DIN VDE 0303	O x cm	>10 ¹⁴
Surface Resistance	DIN VDE 0303	O	>10 ¹³

The above data is based on present knowledge and is given without guarantee.

Existing laws and conditions are to be respected by the user of our products.

PARTWELL LIMITED
CUTTING TECHNOLOGY SPECIALISTS
ORDER TELEPHONE: 01254 671875

T000059U.PPT 1/5 11-04