

SAFETY DATA SHEET

PRODUCT: Orange Plate Cleaner (Wipes)
DATE OF ISSUE: 3rd May 2007
SUPPLIER: Partwell Cutting Technology Specialists
Bridge Works, Stanley Street, Blackburn, Lancs. BB1 3BW
Tel: 01254 671875 Fax: 01254 674823

COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients

	Conc.	CAS	EINECS	Symbols/Risk Phrases
Orange Terpenes	40 – 50%	8028-48-6	232-433-8	Xi; R38 N; R50/53 R10
Isopropanol (Propan-2-ol)	40 – 50%	67-63-0	200-661-7	F; R11 Xi; R36 R67

HAZARDS IDENTIFICATION

Main Hazards:

Flammable

Irritating to eyes and skin

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Vapors may cause drowsiness and dizziness

FIRST AID MEASURES

Skin Contact May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye Contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 mins, holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation Inhalation may cause coughing, tightness of chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.

Ingestion May cause nausea and vomiting. Seek medical attention if irritation or symptoms persist.

General Info In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)

FIRE FIGHTING MEASURES

EXTINGUISHER MEDIA: Carbon Oxides. Alcohol resistant foam.

FIRE HAZARDS: Burning produces irritating, toxic and obnoxious fumes.

PROTECTIVE EQUIPMENT: Wear suitable respiratory equipment when necessary.

HANDLING & STORAGE

HANDLING: Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition – NO SMOKING

STORAGE: Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labeled containers.

HANDLING & STORAGE

EXPOSURE LIMITS:

Isopropanol

WEL 8-hr limit ppm:400

WEL 8-hr limit mg/m³: 999

Packaging instructions (Passenger) 309 Maximum quantity 60 L

REGULATORY INFORMATION

LABELLING: This product is classified in accordance with 67/548/EEC

Symbols: Xi – Irritant; N – Dangerous for the environment

RISK PHRASES:

R10 – Flammable

R36/38 – Irritating to skin and eyes

R50/53 – Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment

R67 – Vapors may cause drowsiness and dizziness

SAFETY PHRASES:

S29 – Do not empty into drains

OTHER INFORMATION

Text of risk phrases in composition and information on ingredients section

R10 – Flammable

R36 – Irritating to eyes

R38 – Irritating to skin

R50/53 – Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment

R67 – Vapors may cause drowsiness and dizziness

The information supplied in this datasheet is designed only as guidance for safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other processes.