

Safety Data Sheet

Ultra Krazi Glue

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name: Ultra Krazi Glue

REACH registered name: Ethyl-2-cyanoacrylate

REACH registered number(s): 01-2119527766-29-XXXX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses of substance/mixture: PC1: Adhesive, sealants

1.3. Details of the supplier of the safety data sheet

Company Name: Partwell Group

Bridgeworks, Stanley St, Blackburn

Lancs, BB1 3BW

Email: info@partwell.com

1.4. Emergency telephone number

Emergency tel: 01254 671875

Section 2: Hazard Identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/37/38

Classification under CLP: STOT SE 3: H335; Eye Irrit. 2: H319; Skin Irrit 2: H315; - : EUH202

Most important adverse effects: Irritating to eye, respiratory system and skin.

2.2. Label elements

Label elements under CLP:

Hazard Statement: H315: Causes skin irritation

H319: Causes serious eye irritation

Safety Data Sheet

Ultra Krazi Glue

H335: May cause respiratory irritation

EUH202: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Signal word: Warning



Hazard pictograms: GHS07: Exclamation mark

Precautionary statements:

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area

P280: Wear protective gloves/protective clothing/eye protection/face protection

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312: Call a POISON CENTRE or doctor if you feel unwell

Label elements under CHIP:

Hazard symbols: Irritant.



Risk Phrases R36/37/38: Irritating to eyes, respiratory system and skin.

Safety phrases:

S2: Keep out of the reach of children

S46: If swallowed, seek medical advice immediately and show this container or label.

Precautionary phrases: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Safety Data Sheet

Ultra Krazi Glue

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHYL-2-CYANOACRYLATE

EINECS	CAS	CHIP classification	CLP classification	Percentage
230-391-5	7085-85-0	Xi: R36/37/38	Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315	>90%

Non-classified ingredients:

HYDROQUINONE

EINECS	CAS	CHIP classification	CLP classification	Percentage
204-617-8	123-31-9	Xn: R40; Xn: R68; Xn: R22; Xi:R41; Sens.: R43; N: R50	Carc. 2: H351; Muta. 2: H341; Acute Tox.4: H302; Eye Dam. 1: H318; Skin Sen. 1: H317; Aquatic Acute 1: H400	<1%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all the contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness. The eyes may water profusely.

Eye Contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Safety Data Sheet

Ultra Krazi Glue

Ingestion: There may be irritation and redness at the site of contact.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed/immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate/special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixtures

Exposure hazards: In combustion emits toxic fumes

5.3. Advice for fire-fighters

Advice for fire-fighters: wear self-contained breathing apparatus. Wear protective clothing to prevent with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS

Safety Data Sheet

Ultra Krazi Glue

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mist in the air

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Polyethylene

7.3. Specific end use(s)

Specific end uses(s): No data available

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ETHYL-2-CYANOACRYLATE

Workplace exposure limit: Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	1.5 mg m ⁻³	-	-

DNEL/PNEC value

Procedure PC07

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	9.25 mg m ⁻³	Workers	Local
DNEL	Inhalation	9.25 mg m ⁻³	Workers	Systematic
DNEL	Inhalation	9.25 mg m ⁻³	General Population	Local
DNEL	Inhalation	9.25 mg m ⁻³	General Population	Local

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand Protection: Protective gloves.

Safety Data Sheet

Ultra Krazi Glue

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Reacts with water.

Also soluble in: Acetone

Viscosity: Viscous

Kinematic viscosity: 700-1000

Viscosity test method: Cone and plate @ 25 °C (CPs)

Boiling point/range / °C : >149

Melting point/range / °C : No data available.

Flammability limits / %: lower: No data available.

Flammability limits / %: Upper: No data available.

Flash point / °C : 80.0-93.4

Part. Coeff. N-octanol/water: No data available.

Auto flammability / °C : 450

Vapour pressure: <700 mbar

Relative density: 1.05

pH: Not applicable.

VOC g/l: <20

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

Safety Data Sheet

Ultra Krazi Glue

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

19.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.2. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions

10.4. Conditions to avoid

Conditions to avoid: Moist air. Heat

10.5. Incompatible materials

Materials to avoid: Water. Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. Decomp. Products: In combustion emits toxic fumes

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
DERMAL	RBT	LD50	>2000	mg kg ⁻¹
ORAL	RAT	LD50	>5000	mg kg ⁻¹

Hazardous ingredients:

ETHYL-2-CYANOACRYLATE

ORL	RAT	LD50	>5	ml kg ⁻¹
-----	-----	------	----	---------------------

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT INH DRM	Hazardous: calculated

11.2. Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Safety Data Sheet

Ultra Krazi Glue

Eye contact: The may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat .

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effect: Immediate effects can be expected after short-term exposure.

Section 12: Ecological Information

12.1. Toxicity

Eco toxicity values: No data available

12.2. Persistence and degradability

Persistence and degradability: Biodegradable

12.3. Bio accumulative potential

Bio accumulative potential: No bio accumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible eco toxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialist disposal company.

Waste code number: 08 94 09

NB: The user's attention is drawn to the possible existence of regional or nation regulations regarding disposal.

Section 14: Transport information

14.1. UN number

Safety Data Sheet

Ultra Krazi Glue

UN number: UN3334

14.2. UN proper shipping name

Shipping name: AVIATION REGULATED LIQUID, N. O. S. (ETHYL-2-CYANOACRYLATE)

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental Hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

Section 16: Other information

Other information: This safety is prepared in accordance with Commission Regulation (EU). No 453/2010.

*indicated text in the SDS which has changed since in the last revision.

Phrases used in s.2 and s.3: EUH202:

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

Safety Data Sheet

Ultra Krazi Glue

H341: Suspected of causing genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure causes the hazard>

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>

H400: Very toxic to aquatic life.

R22: Harmful if swallowed.

R36/37/38: Irritating to eyes, respiratory system and skin

R40: Limited evidence of a carcinogenic effect.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R50: Very toxic to aquatic organisms.

R68: Possible risk of irreversible effects

Legend to abbreviations:

PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

Ham = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

Safety Data Sheet

Ultra Krazi Glue

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: All the above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be liable for any damage resulting from handling or from contact with the above product.