

MATERIAL SAFETY DATA SHEET

PRODUCT	GLASS FIBRE REINFORCED TAPE
REF	DM0170
DATE OF ISSUE	January 2007
SUPPLIER	Partwell Cutting Technology Specialists Bridge Works, Stanley Street, Blackburn, Lancs. BB1 3BW Tel: 01254 671875 Fax: 01254 674823
DESCRIPTION	Crossweave glass-fibre reinforced tape coated with a synthetic rubber resin adhesive (hotmelt)
APPLICATION	Strapping, Bundling, Carton Sealing
TECHNICAL DETAILS	
Total thickness	0.125 mm
Backing thickness	0.03mm
Tensile strength	240 n/cm
Elongation	10%
Temperature	0°C to 60°C
Steel adhesion	5 n/cm
Colours	Clear

Note:

Unless otherwise specified, the figures above are average values and should not be treated at face value for specification purposes. The company reserves the right to improve products, and any change in specification will result in re-issue of the information sheet. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modification or otherwise. Please check that you have the latest issue of the information sheet. All slitting and length tolerances are to British standards.

**PRESS CUTTING
TECHNOLOGY**

**DIE MAKING
SUPPLIES**

**PLASTIC
ENGINEERING**

**FOOD RELATED
PRODUCTS**

www.partwell.com

One stop shop for Die Making, Die Cutting and Print Finishing supplies