

PLASTIC SHEET PET(G)

Thermoplastic Polyester

PHYSICAL PROPERTIES

Density	DIN 53479	g/cm ³	1.77
Tensile Strength at yield	DIN 53455	N/mm ²	50
Tensile Strength	DIN 53455	N/mm ²	26
Notched Impact Strength	DIN 53453	kJ/m ²	16
Operating Temperatures	Max	°C	65
	Min	°C	-40
Moisture absorption	24hrs in	%	0.2
	water 23°C		
Rockwell Hardness Test	ASTM D785	Class	R104-117
Elongation at Yield	DIN 53455	%	5
Tensile Modulus of Elasticity	DIN 53457	N/mm ²	2050

Technical Data Sheet

FURTHER INFORMATION

Electrical Properties

Volume Resistivity	DIN 53482	Ω*cm	10 ¹⁵
--------------------	-----------	------	------------------

Thermal Properties

Co efficient Linear Thermal Expansion		Mm/m°C	0.050
---------------------------------------	--	--------	-------

Fire Behaviour

Flammability 3mm sheet	V-2 ⁽⁶⁾	rating	UL94
------------------------	--------------------	--------	------

PRESS CUTTING
TECHNOLOGY

DIE MAKING
SUPPLIES

PLASTIC
ENGINEERING

FOOD RELATED
PRODUCTS

www.partwell.com

Plastic Engineering Specialists:

DESIGN ASSISTANCE | 3D SOFTWARE | CNC ENGINEERING PLASTICS | 5-AXIS CNC TECHNOLOGY
 WATER JET CUTTING | RAPID PROTOTYPING | ANY VOLUME PRODUCTION | INDUSTRIAL PLASTIC STOCKIST